

Product sheet

power2 S3



Product reference	POWER2
Euronorm EN345	S3 SRC
Sizes	38-47
Weight(s. 41)	760 gr.

Model Description: Full grain leather shoe, water repellent, black, Nylon mesh lining, antistatic, puncture resistant kevlar sole, shock proof, anti-slip, composite toe, S3, PU/rubber sole.

Application areas: : construction, industries

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, neither nearby a heat source.

		Description	Measure unit	Result	EN345 required
Complete shoe	Protection of toes: composite tip resistant to: » a shock of 200 J » pressure of 1500 kg	Impact resistance (Clearance after Shock)	mm	19,5	>14
		Compressive strength (after clearance compression)	mm	20,5	>14
	Anti-Shock system: Low-Density polyurethane And profile of the heel	Shock absorption in heel	J	>27	>20
Upper	full grain leather, water repellent, black	Permeability to water vapor	mg/m ² hour	>4,9	>0,8
	thickness 1,6mm	Permeability coefficient	mg/cm ²	>45,1	>20
	Protection of the anchor	Water repellent	minute	>90	<60
Front	Thickness 1,2mm	Permeability coefficient	mg/cm ²	>41,5	>30
Lining	Nylon mesh black	Permeability to water vapor	mg/cm ² hour	>5	>2
Back	Thickness 1,0mm	Permeability coefficient	mg/cm ²	>45	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	cycles	>400	>400
Outsole	Antistatic double density polyurethane injected directly onto the PU/TPU upper	Abrasion resistance(volume loss)	mm ³	110	<150
	black, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance(volumen variation AV)	%	+1,0	<+12
		Coefficient of adhesion of the outsole	---	0,19	>0,15

Our shoes are constantly evolving, the technical data above may change.

All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.